TRELLJET 681 Antimicrobial

Protection

INDUSTRIAL MAINTENANCE

Jetting, draining and spraying hoses



Applications

Specially designed for professional and industrial high pressure cleaning.

The antimicrobial TRELLJET 681 is suitable for all environments where bacteria are concerned: cleaning companies, food industries, pharmaceutics, packaging/bottling, health care institutions, schools, etc.

Suitable for mobile pressure washers, fixed installations and reel mounted applications

Advantages

- Crush resistant.
- Antimicrobial protection: prevents odor, stain, degradation and breakdown from bacterial attacks.
- Non-staining smooth cover.
- Oil, detergents, wear and weather resistant.
- High temperature resistance.
- Highly flexible and kink resistance.
- Long service life.

Technical description

Inner tube: NBR/SBR, black, smooth.
Reinforcement: synthetic textile.
Cover: NBR/SBR, blue, smooth.

Temperature range: - 40 °C to + 120 °C.

Special properties: Antimicrobial protection in reference to :

ISO 22196:2007 (Quantitative analysis of Bacterial growth).

AATCC 30-2004 (Qualitative analysis to evaluate the antimicrobial activity of fungicides).

Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

Complementary information

Available in random lengths: 10-95 m.

ND	ID		Wall thickness	OD		Reinforcement diameter		Working pressure		Bending radius	Weight	Length	Notes
	4	mm	mm	mm		mm		bar	bar	mm	kg/m	m	
10	9.5	+ 0.6/- 0.2	4.5	18.5	± 0.8	15.0	± 0.3	200	500	60	0.29	100 *	
13	12.7	+ 0.8/- 0.4	4.5	21.7	± 0.6	18.3	± 0.3	200	500	70	0.40	100 *	

^{* 50 %} of the volume in each delivery will be random lengths, shortest length of 10 m, at least 50 % will be in fixed length mentioned in the table.

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Embossed branding: TRELLEBORG - TRELLJET 681 - ND mm - ND " - WP 200 BAR/2900 PSI - MAX 120 °C - quarter/year - Made in France

Branding:

