



Applications

For pneumatic tooling or pneumatic control lines (e.g. paint spray guns).

Advantages

- Static conductive tube.
- Very flexible hose especially at low temperatures.
- Suitable for hot water.

Technical description

Inner tube: EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, blue, smooth.

Temperature range: - 40 °C to + 100 °C.

Electrical properties: conductive tube, $R < 10^6 \Omega/m$.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
6.0	± 0.4	3.0	12.0	± 0.5	20	80	25	20 - 40 - 120
7.0	± 0.5	3.5	14.0	± 0.6	20	80	25	20 - 40 - 120
8.0	± 0.5	3.5	15.0	± 0.6	20	60	30	20 - 40 - 120
9.0	± 0.5	3.5	16.0	± 0.6	20	60	35	20 - 40 - 120
10.0	± 0.5	4.0	18.0	± 0.6	20	60	40	20 - 40 - 120
12.0	± 0.6	4.0	20.0	± 0.7	20	60	60	20 - 40 - 120

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding: