

# SABLEX

## CONSTRUCTION AND ENVIRONMENT

Blasting and guniting



### Applications

For cleaning and shot blasting castings, metal, stone, and concrete surfaces.

### Advantages

- Small tolerances, therefore easy to couple.
- Longitudinally stable i.e. the length will not alter under pressure (unstable hoses result in the operator losing control when pressure is applied).
- Light weight and flexible for easy handling.
- Conductive inner tube compound gives increased safety for the operator, since there is no risk of wire breakage in use.

### Technical description

**Inner tube:** wear resistant NR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** weather and abrasion resistant SBR, black, fabric impression.

**Temperature range:** - 30 °C to + 70 °C.

**Electrical properties:** conductive tube,  $R < 2 \cdot 10^6 \Omega/m$ .

**Special properties:** abrasion resistance of tube  $< 70 \text{ mm}^3$  according to ISO 4649.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
<b>13.0</b>	7.0 ± 0.5	27.0 ± 1.0	12	40	65	0.58	<b>40</b>	
<b>16.0</b>	7.0 ± 0.5	30.0 ± 1.0	12	40	80	0.68	20 - 40	
<b>19.0</b>	7.5 ± 0.5	34.0 ± 1.0	12	40	100	0.78	<b>20 - 40</b>	
<b>25.0</b>	7.0 ± 0.5	39.0 ± 1.0	12	40	125	0.86	<b>20 - 40</b>	
<b>32.0</b>	8.0 ± 0.5	48.0 ± 1.0	12	40	160	1.30	<b>20 - 40</b>	
<b>32.0</b>	11.0 ± 0.5	54.0 ± 1.0	12	40	140	1.85	20 - 40	
<b>35.0</b>	9.0 ± 0.5	53.0 ± 1.0	12	40	190	1.57	40	
<b>38.0</b>	10.0 ± 0.5	58.0 ± 1.0	12	40	170	1.89	<b>20 - 40</b>	
<b>40.0</b>	10.0 ± 0.5	60.0 ± 1.0	12	40	180	1.97	<b>20 - 40</b>	
<b>42.0</b>	9.0 ± 0.5	60.0 ± 1.0	12	40	240	1.81	20 - 40	
<b>50.0</b>	10.0 ± 0.75	70.0 ± 1.5	12	40	250	2.36	<b>40</b>	
<b>63.0</b>	10.0 ± 0.75	83.0 ± 1.5	12	40	325	2.90	40	
<b>65.0</b>	10.0 ± 0.75	85.0 ± 1.5	12	40	320	2.95	20 - 40	
<b>76.0</b>	10.0 ± 0.75	96.0 ± 1.5	12	40	400	3.42	40	
<b>102.0</b>	10.0 ± 0.75	122.0 ± 1.5	12	40	550	4.40	40	

Length in green = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

**SABLEX**



**TRELLEBORG**