



VOLUKLER

OIL & GAS

Oil and petroleum/Discharge applications

For equipment of petrol pumps: regular, super and unleaded petrol, biofuel, diesel fuel.

Advantages

- Good resistance to ageing and abrasion from repeated dragging over oily floors.
- Complies with European standard.
- Can be supplied ready fitted and tested with end fittings.

Technical description

Inner tube: petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile, braided.

Cover: oil and weather resistant NBR/PVC, black, smooth.

Temperature range: -30°C to +55°C.

Electrical properties: conductive tube, $R < 10^6 \Omega/\text{lg}$.

Standard/Approval:

EN 1360:2013 type 1.

ID 21mm: also available as VOLUKLER VR ASSEMBLY with internal vapour recovery tube for petrol dispensing systems, compliant with EN 13483:2013/1, consult us.

Complementary information

Blue, red or green cover upon request.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
16.0	±0.8	4.5	25.0 ±0.9	16	48	80	0.40	40 - 80 - 120
19.0	±0.8	6.0	31.0 ±0.9	16	48	100	0.63	40 - 80 - 120
21.0	±0.8	6.0	31.0 ±0.9	16	48	75	0.55	40 - 80
25.0	±0.9	6.0	37.0 ±0.9	16	48	140	0.75	40 - 80

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

TRELLEBORG - VOLUKLER - EN 1360:2013 - TYPE 1 - ND - 16 BAR - Ω - quarter/year - batch number - Made in France

