


**KD 不锈钢绞接式接头 (WH/TH) 弹性密封圈**

用于宽孔口平面油口


 X1) PTFE 密封  
 X2) 支撑环 (不锈钢)

**D**

用于 WH 和 TH	用于 螺纹	D1	D2	L1	重量 克/件	订货号
06LRKD71	G 1/8 A	10.0	17.0	2.5	2	<b>KD1/871</b>
08LR/06SRKD71	G 1/4 A	13.5	22.0	3.0	4	<b>KD1/471</b>
10LR/08SRKD71	G 1/4 A	13.5	22.0	3.0	4	<b>KD1/471</b>
12LR/10SRKD71	G 3/8 S	17.1	27.0	3.0	6	<b>KD3/871</b>
12SRKD71	G 3/8 A	17.1	27.0	3.0	6	<b>KD3/871</b>
15LR/14SRKD71	G 1/2 A	21.4	32.0	4.5	12	<b>KD1/271</b>
18LR/16SRKD71	G 1/2 A	21.4	32.0	4.5	12	<b>KD1/271</b>
22LR/20SRKD71	G 3/4 A	26.8	41.0	3.5	17	<b>KD3/471</b>
28LR/25SRKD71	G 1 A	33.5	46.0	3.5	17	<b>KD171</b>
35LR/30SRKD71	G 1 1/4 A	42.4	57.0	3.5	26	<b>KD11/471</b>
42LR/38SRKD71	G 1 1/2 A	48.4	64.0	3.5	35	<b>KD11/271</b>
06LMKD71	M 10×1	10.3	17.0	2.5	2	<b>KD1071</b>
08LM/06SMKD71	M 12×1.5	12.3	22.0	3.0	5	<b>KD1271</b>
10LM/08SMKD71	M 14×1.5	14.3	22.5	3.0	5	<b>KD1471</b>
12LM/10SMKD71	M 16×1.5	16.4	27.0	3.0	9	<b>KD1671</b>
15LM/12SMKD71	M 18×1.5	18.4	29.0	3.0	9	<b>KD1871</b>
14SMKD71	M 20×1.5	20.4	32.0	3.0	9	<b>KD2071</b>
18LM/16SMKD71	M 22×1.5	22.4	32.0	4.5	12	<b>KD2271</b>
22LMKD71	M 26×1.5	26.4	41.0	3.5	18	<b>KD2671</b>
20SMKD71	M 27×2	27.4	41.0	3.5	18	<b>KD2771</b>
28LM/25SMKD71	M 33×2	33.5	46.0	3.5	17	<b>KD171</b>
35LM/30SMKD71	M 42×2	42.4	57.0	3.5	26	<b>KD11/471</b>
42LM/38SMKD71	M 48×2	48.4	64.0	3.5	35	<b>KD11/271</b>